

DIY Texture

INTERIOR & EXTERIOR USE

Base Colors – Grey & White Product

DIY Texture is a single component polymer cement coating designed for a rich textured surface. DIY Texture is designed to be applied by hand trowel, allowing the user to be creative with the look and feel of the top surface. DIY Texture can also be used along with fiber tape or hand carving for creating patterns.

Transform damaged, worn or unsightly concrete into a fresh new surface.

Coverage per 25LB Box

Thin Troweled application ----- 1/16" thickness – 50 SF

Medium Troweled application ----- 1/8" thickness – 25SF

Deep Troweled application ----- 1/4" thickness – 12SF

** Do not exceed 1/4" thickness per coat/application.

Tools & Supplies Supplies: clean bucket, low-speed drill with mixing paddle, spikes

Application tools: pool trowel, margin trowel, fresno trowel, drywall sprayer, Magic Trowel

Surface Preparation

Surface and ambient temperatures should be between 50°F and 90°F during application and curing. The coating must remain above freezing for a minimum of 48 hours after application. Contaminants and curing agents must be completely removed. Failure to remove all contaminants can result in loss of adhesion. Concrete must reach at minimum a surface texture resembling 220 grit sandpaper.

INTERIOR SMOOTH FINISHED SURFACES:

Option A > Diamond Grinding -- use 80 – 150 grit metal bond diamonds to roughen the top surface. Scrub the surface using DIY Degrease, vacuum and rinse.

Option B > Chemical Etch – if needed, remove oil and grease using DIY Degrease, scrub and rinse. Apply DIY Surface Etch at a dilution ratio of 4 parts water to 1 part Surface Etch. Scrub in with a stiff bristle broom. When the fizzing action stops, apply baking soda to neutralize (dilution of one box in 5 gallons hot water) using a stiff bristle brush or broom to scrub in the neutralizing solution then rinse with water. Do not allow the etching solution to dry on the concrete prior to neutralizing. If a more porous surface is needed, repeat the DIY Surface Etch application process.

EXTERIOR BROOM FINISHED SURFACES: 1. If needed, remove oil and grease using DIY Degrease. 2. Pressure wash and rinse. 3. Apply DIY Surface Etch at a dilution ratio of 4 parts water to 1 part Surface Etch. Scrub in with a stiff bristle broom. 4. When the fizzing action

stops, apply DIY Neutralize (dilution of 8 oz in 5 gallons water) using a stiff bristle brush or broom to scrub in the neutralizing solution then rinse with water. 5. Do not allow the Surface Etch solution to dry on the concrete prior to neutralizing. If a more porous surface is needed, repeat the DIY Surface Etch application process.. Pressure wash. ***Dispose of all waste water in accordance with local, state, and federal regulations.

Holes & Patching

Fill all holes deeper than 1/16" with appropriate concrete repair material. Patch and allow to cure 30 minutes prior to coating the entire floor with DIY Texture.

Mixing

Measure 4 quarts of clean water and pour into a clean mixing bucket. Gradually add the dry mixture while mixing using a low-speed drill equipped with a smooth sided mixing paddle. Mix thoroughly so that no lumps or dry powder remain. Up to an additional quart of water can be added to reach desired consistency. Allow to stand 5 minutes then remix. Always mix on low speed...high speed mixing will entrain air bubbles into the mixture.

Integral Color

When using an integral color pack, add the color pack contents to the water in the mixing bucket before adding DIY Texture.

Application

Apply a light mist of clean water to the concrete surface. Do not allow the water to puddle. The dampening of the slab keeps the concrete from pulling the water from the DIY Texture mixture. Premature drying or water loss will result in a low strength, cracked and or crusty coating.

Cure Rate/Drying Time

Thickness of application, temperature, and humidity will affect cure rate. Surface will exhibit uniform appearance when dry. Approximate dry times: 6-12 hours to re-coat, 12-24 hours to stain. Full cure 3-7 days.

Clean Up

Use water to immediately and completely clean all tools that come in contact with DIY Texture. Dispose of waste water in accordance with federal, state and local regulations.

Limitations

DIY Texture is for use on stable concrete, it will reflect moving cracks and expansion joints. Prepare a sample prior to application. As with other cement and masonry products, DIY Texture will stain and tire mark if left unsealed. It is the sole responsibility of the property owner and/or applicator to determine the suitability and safety of this product.

Staining

Surfaces to be stained must be clean and free of all dirt and contaminants. DIY Texture must cure for a minimum of 12 hours prior to staining. Surface will exhibit a uniform appearance when

dry. Follow label directions and technical data sheets for stain application. Color may vary from color chart. Prepare a test section for approval.

Storage and Shelf Life

Keep away from children. Avoid freezing temperatures and excessive heat. Protect from moisture. Unopened containers may be stored for up to one year from the date of manufacture.

Safety

Wear protective respiratory gear when handling dry portions of DIY Texture. Avoid contact with eyes and prolonged contact with skin. DIY Texture contains silica and Portland cement. Portland cement can cause alkali burns. Use with adequate ventilation. When using in confined or limited ventilation areas, use respirator to protect against breathing vapors and particles. Use proper safety apparel including but not limited to gloves, eye protection, respirator and protective clothing.

First Aid

- Eyes—Do not rub eyes. Flush immediately with water holding eyelids apart.
- Skin—Wash affected areas thoroughly with soap and water
- Inhalation—Move to fresh air. If symptoms persist, seek medical attention
- Internal—Contact a physician immediately

Warranty

The Manufacturer and/or the Seller warrants that if any goods supplied prove defective in workmanship or material, that Manufacturer and/or Seller shall replace them or refund the purchase price. This warranty is made in lieu of any and all other warranties expressed or implied. Before application, the User shall determine the suitability of the product for his intended use and User assumes all risks and liabilities whatsoever in connection therewith. Under no circumstances shall the Manufacturer and/or Seller be liable for incidental, consequential or other damages for alleged negligence, breach of warranty, or strict liability arising out of use or handling of this product. The sole liability of Manufacturer and/or Seller for any claims arising out of the use or sale of the product shall be for the User's purchase price. Any claim of defective product must be received in writing within one (1) year from date of shipment. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN